



## STANDARD COLOR

## SPECIAL COLOR

## LINE MARKING



RAL 1014 IVORY



RAL 1015 LIGHT IVORY



RAL 5012 LIGHT BLUE



RAL 6021 PALE GREEN



RAL 7000 SQUIRREL GREY



RAL 7035 LIGHT GREY



RAL 7040 WINDOW GREY



RAL 9010 PURE WHITE



RAL 1019 GREY BEIGE



RAL 5015 SKY BLUE



RAL 5012 LIGHT BLUE



RAL 7030 STONE GREY



RAL 7037 DUSTY GREY



RAL 3013 TOMATO RED

**DUBAI**  
**ABU DHABI**  
**ITALY**

T. +971 4 8803488 F. +971 4 8803450  
T. +971 2 5511949 F. +971 2 5511949  
T. +39 75 9221297 F. +39 75 9221174



RAL 1023 TRAFFIC YELLOW



RAL 9016 TRAFFIC WHITE



RAL 5017 TRAFFIC BLUE



RAL 3020 TRAFFIC RED



RAL 6024 TRAFFIC GREEN

The colours in this chart is just indicative. Whilst every effort has been made to display the colours accurately, no guarantee is given or implied as to the accuracy of this colours. In critical situations, a trial should be laid to compare the actual product against the desired colour. Require an applied sample prior to order confirmation. Other colours are available depending on quantity and lead time.

All RAL Nos. are from Universal RAL Color Chart.



## FLOORING PRODUCTS

### MONNELI EPOFLOOR E 100

A two component solvent based epoxy floor coating. It forms a smooth semi gloss tough finish that has very good resistance to abrasion and chemicals. (Colour chart applicable for dark colours only)

### MONNELI EPOFLOOR E 250

A two component solvent free epoxy system consisting of a coloured base resin and hardener. (All colours listed in the colour charts are available)

### MONNELI EPOFLOOR E 2000

High build solvent free epoxy flooring system designed as a medium to heavy epoxy coating system used in basements, and ground floor car parks which exhibits little or no structural movements. (All colours listed in the colour chart are available)

### MONNELI EPOFLOOR ECT

A three component solvent free protective coating system based on coal tar modified epoxy resin. Heavy duty, anti-skid surface dressing (Available in black colour only)

### MONNELI EPOFLOOR SLE 25

A two component solvent free high performance pigmented self leveling epoxy flooring with thickness from 0.5-2.5mm. (All colours listed in the colour chart are available)

### MONNELI EPOFLOOR SLE 50

A three component solvent free self leveling epoxy flooring composed of epoxy resin, hardener, silica and color pack. It is for thickness from 2.5-5.0mm.

### MONNELI EPOFLOOR HM

High performance epoxy floor screed (Can be coated with any coloured floor coating on top of the screed if necessary)

### MONNELI EPOFLOOR P 125

Polyurethane coating for concrete floors supplied in two components. (Colour charts applicable for dark colours only)

### MONNELI EPOFLOOR P 200

A solvent free and odorless high build flexible polyurethane floor coating with outstanding impact and chemical resistance with elastomeric properties.

### MONNELI EPOFLOOR P 1100

Seamless flexible polyurethane flooring system designed to be applied for commercial, semi-industrial and institutional applications. It provides high durability, good mechanical strength and abrasion resistance.

### MONNELI EPOFLOOR P 1200

Seamless, heavy duty, multi layer and UV resistant flexible polyurethane flooring system used for the protection of concrete floors subject to high levels of traffic, impact and abrasion.

### MONNELI EPOFLOOR P 1140

Multi-layered, seamless UV stable polyurethane traffic deck coating system. It is designed for floors where superior impact and wear resistance are required.

### MONNELI EPOFLOOR P 1150

Protective, polyurethane based traffic deck coating system providing a seamless and profiled wear resistant surface for traffic areas. (Colour chart applicable for dark colours only)

### MONNELI EPOFLOOR P 1160

UV stable waterproofing and protective polyurethane based traffic deck coating system used for exposed and intermediate traffic decks where crack bridging and waterproofing properties are required.

### MONNELI EPOFLOOR P 2500

Flexible, skid-proof, water tight protection flooring system designed to create a remarkable protection for both new and existing heavily trafficked areas which requires excellent chemical resistance. (Top coat Epofloor UV2 which is included in the system is available in all colours)

### MONNELI EPOFLOOR SLP 25

Solvent free self leveling polyurethane floor topping for use in concrete or steel substrates with thickness of 0.5-2.5mm.

### MONNELI EPOFLOOR SLP 50

Solvent free self leveling polyurethane floor topping for use in concrete or steel substrates with thickness of 2.5-5mm.

### MONNELI EPOFLOOR UV2

Two component UV resistant aliphatic polyurethane coating. It is UV stable for use in exterior applications, cures rapidly and acts as an ideal sealing system against weather exposure. (All colours listed in the colour chart are available)

### MONNELI EPOFLOOR TX

Heavy duty solvent free high performance polyurethane floor screed designed to provide excellent resistance to abrasion and chemical attack. It is designed for applications at nominal thickness from 6.0-9.0mm. (Can be coated with any coloured floor coating on top of the screed if necessary)

### MONNELI EPOFLOOR LM

A specially formulated fast drying line marking paint that can be applied in one coat for marking lines on concrete, asphalt, epoxy or polyurethane surfaces.